

## Proposed Code Change State Form 41186R

RETURN TO: INDIANA DEPARTMENT OF HOMELAND SECURITY CODE SERVICES SECTION 302 W. Washington Street Room W246

Indianapolis, IN 46204

INSTRUCTIONS:

Only TYPED copy accepted.

(KEY – Dashed line through material to be deleted, underline material to be added)

FOR OFFICE USE ONLY

Received 5/18/09

Code 15.6-09

Use second sheet for any material requiring more space.			
Code Title		Edition	
International Residential Code		2009	
Section number and title		Page	
Table R301.5 Min. Uniformly Distributed Live Load		48	
Proponent Title			
Joe Heinsman Technical Services Manager		l .	
Address		Phone	
2801 N. Morton Street		317-738-3211	
PROPOSED CODE CHANGE (Check One)			
Change to read as follows Add to read as follows			
xx Delete and substitute as follows	elete without substitution		
Delete from the third row under USE "and attics served with fixed stairs".  Change footnote b to read as follows: Attics with limited storage are those having a minimum clear height of greater than 6 feet, are served by a door or disappearing or permanent stairway, and do not meet the definition of a Habitable attic.  Delete footnote g.  Add a footnote i to read as follows: This live load need not be considered as acting concurrently with any other live load. Add a reference to footnote i at the end of the text in the first row under USE "Attics without storage".			
REASON AND FISCAL IMPACT			
Requiring a 30 psf load for any attic area regardless of size or shape when served by a stairs is a poor idea. Very low/small attics areas or raised/sloped ceiling areas that are off the main attic area for which the stairs is intended would require the 30 psf load. The size and shape of the attic area needs to be considered in all cases when determining load.			
The new limited storage requirements with the 42" clear height are old BOCA language. They were not in the 2000 or 2003 IRC even though they had been around for a long time. Indiana used the UBC and never had this requirement. There is no evidence for a problem with performance for the many years and in the many states that have never had this requirement. There is no evidence that this language created better performance of roof/ceiling construction in BOCA states.			
The current definition for a limited storage attic has been used for a long time with no demonstration of any problem.			
The end of footnote g also has a requirement for a minimum 10 psf dead load that this would eliminate. This requirement is in direct contradiction to R301.4 which states that the "actual weights of materials and construction" are to be used to determine dead loads. Using the actual weights of materials and construction is how it has always been done in this state and again there is no evidence of a problem.			
Fiscal impactNone			
REVIEW RECOMMENDATION			
Approve 18-3-3 6/11/09			
Disapprove			
Approve as amended			
Further Study	Further Study		